

THX product family upgrade procedure

Note: We suggest downloading the settings from the unit before upgrade.

- 1. **<u>Switch OFF</u>** the power supply.
- 2. Take off the front lid and switch the battery backup off



3. Press and hold the "OK" button.





4. Connect the unit to PC via male-male USB cable.



- 5. Wait few seconds and release the button.
- 6. The unit should enumerate as a "BOOTLOADER" USB Mass Storage

au au air an										
COTO - Consultar - BOOTLGADER BIC				- in Seath	it 19					
The fidt New Trols Islp										
Departure + there with + them false finder				建 •						
H in texteens	hane *	Data motified	TYTM	100						
Codia: Contracts Contracts Contracts Contracts Powert Siless Contracts		100-1000 05 20	Text Document	010						
1 kan										

7. Open the "BOOTLOADER" folder and drag-n-drop the s19 file.

Computer	· BOOTLOADER (b)					• 🖛	Search B	
Pin Edd. Ymw Todit	Help							
Organize • Share with •	Burn New Folder						•	•
Favorites	Name *		Date modified 18/04/2008 09:20	Type Text Document	Size 0 KB			
Doverloads	1000L_1_4.519		02/11/2012 14:13	519 File	887 KB			
Documents		C 15 Seconda ran	(and rp)					
Pictures Videos		from output (Cr) About 15 Second	projects\THEN/CODE\TH	.(output) to BOOTLOA	DER (I;)			
Computer		More details		Ca	ncet			
BOOTLOADER (1:)								
🗣 Network								
								_



- 8. After copying file has been completed, disconnect the cable.
- 9. Switch the battery backup ON
- 10.Close the lid and switch the power ON

Warning: Always <u>disconnect</u> power supply from the unit before opening the lid.

